DL 100 READY TO USE



CHARACTERISTICS

- Ready to use tooling agent
- Ready made solution: the product has already been brought to concentration and can be sprayed directly on the surface without diluting
- Completely pH-neutral
- Non agressive to the joint
- Does not leave stains after rinsing with water
- Does not contain solvents or acids
- Does not affect the surface.

APPLICATIONS

 To smooth the surface of fresh applied sealant such as silicone, polymer and polyurethane

TECHNICAL CHARACTERISTICS	
Physical and chemical properties	Neutral
Colour	Yellowish
Odour	Neutral
рН	Ca 7,5
Density (20°C)	Ca 1,065 g/ml
Shelf life, in the original packing in dry conditions between +5°C - +25°C	Min. 12 months

PACKING AND COLOURS

12 spray bottles of 500 ml/box - 48 boxes/pallet

METHOD OF USE

Application

- Spray the tooling agent directly on the joint
- Wet the finger or a smoothing tool with the product and smooth the joint.

SAFETY

Safety data sheet available on request.

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore, tests are necessary. Our general conditions apply.

